



2040-80

Recessed Self-Luminous Exit Sign

DATE: [REDACTED]	COMMENTS: [REDACTED]
PROJECT [REDACTED]	

FEATURES

- Requires no electricity, external light source, lamps, batteries, or wires resulting in easy install and no maintenance.
- Approved for floor proximity or above-door applications.
- Designed to be tamper-proof.
- Approved for use in damp, wet, hazardous, and extreme temperature locations.
- Custom wording and pictograms are available upon request.
- 10 or 20 year service life options are available.



CLICK THE IMAGE TO VIEW ALTERNATE PRODUCT PHOTOS
Only available with Adobe Acrobat and Acrobat Reader

ORDERING INFORMATION 2040-80-10-1-BK-BA-MRW

1. SERIES	2. SERVICE LIFE	3. FACE COUNT	4. FACE COLOR	5. FRAME COLOR	6. MOUNTING	7. OPTIONS
2040-80	-	1	-	-	MRW	-
	10 10 Year 20 20 Year	1 Single	BK Black G Green R Red BZ Bronze	BA Brushed Aluminum BK Black WH White BZ Bronze	MRW Recessed Wall Mount	BLANK = NO OPTION CW Custom Wording

ACCESSORIES; ORDER SEPARATELY

- WG-20.0LX19.0WX9.0D = Wireguard, Length: 20", Width: 19", Depth: 9"
- WG-26.0LX19.0WX9.0D = Wireguard, Length: 26", Width: 19", Depth: 9"

SPECIFICATIONS

CONSTRUCTION

- Brushed aluminum recessed pan
- Aluminum stencil with 0.375" polycarbonate cover.

LETTERS

- 6" high; 0.75" stroke

ARROWS

- Universal chevrons

VIEWING DISTANCE

- 100 foot visibility rating

TECHNOLOGY

- Isolite Self-Luminous Signs are illuminated with a light source that consists of glass tubes which are internally coated with phosphor and filled with tritium gas, a natural hydrogen isotope.

ROUGH-IN SIZE

- 12.875" x 8.375"

WEIGHT

- 6 lbs

TEMPERATURE RATING

- From -67°F to 176°F

APPROVALS

- UL Listed to standard UL 924 & CAN/ULC-S572
- NFPA 101 Life Safety Code
- NEC Article 500, Class I, II, and III conditions

WARRANTY

- Our self-luminous products are warranted against any defects in material or workmanship for the rated life of the product. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.

DIMENSIONS

