



# DTH - Dual Tech Hybrid Exit

Photoluminescent/LED Die-Cast Exit Sign

DATE: [REDACTED]	COMMENTS: [REDACTED]
PROJECT [REDACTED]	

## FEATURES

- Internal LEDs are used to charge the photoluminescent material internally for an eco-friendly solution.
- Maintenance-free LED light source illuminates the letters in normal AC power.
- Non-electrical photoluminescence illuminates the letters when AC power fails.
- Requires only 2 watts of power to operate.
- Eliminates the need for any auxiliary power, batteries, or external charging light sources.
- Polycarbonate security cover and wire guards are available.
- Vandal resistant and tamper proof polycarbonate shield are available.
- Recessed power supply is provided for all units.
- Zero current, low-voltage disconnect used to prevent battery from being overly discharged.
- Unique electronic driver circuit provides current control and protection, ensuring optimum LED efficiency and long life expectancy.
- 120/277 VAC with field selectable inputs.
- UL listed for use in damp locations.



CLICK THE IMAGE TO VIEW ALTERNATE PRODUCT PHOTOS  
Only available with Adobe Acrobat and Acrobat Reader

## ORDERING INFORMATION *DTH-G-1-BA-BA-MB*

1. SERIES	2. ILLUMINATION	3. FACE COUNT	5. FACE & FRAME COLOR
DTH	G	-	-
	G Green	1 Single 2 Double	BA-BA All Brushed Aluminum BA-BK Brushed Aluminum Face / Black Body BA-WH Brushed Aluminum Face / White Body BK-BK All Black WH-WH All White CC Custom Color
6. MOUNTING	7. OPTIONS		
MB Back Mount MRW Recessed Wall Mount MPA 12" Swivel Pendant Kit MPB 24" Swivel Pendant Kit MPC 36" Swivel Pendant Kit MPD 48" Swivel Pendant Kit MTEB Top/End/Back Mount	BLANK = NO OPTION TP Tamper proof Screws VRA Vandal Resistant Lens (1/8 in) (Incl. TP) VRB Vandal Resistant Lens (1/4 in) (Incl. TP)		

## ACCESSORIES; ORDER SEPARATELY

- WG-16.5LX14.0WX6.0D** = Wireguard, Length: 16.5", Width: 14", Depth: 6"
- WG-20.0LX19.0WX9.0D** = Wireguard, Length: 20", Width: 19", Depth: 9"
- WG-26.0LX19.0WX9.0D** = Wireguard, Length: 26", Width: 19", Depth: 9"

## SPECIFICATIONS

### CONSTRUCTION

- Injection molded internal cavity reflector provides easy installation and maintenance with perfectly even legend illumination.
- Two piece, heavy-duty walls are constructed from die cast aluminum alloy.
- Front stencil face has an overlapping light seal for no light leakage.
- Hidden knock out access points with a universal pattern.
- Recessed frame, polycarbonate face shields with tamper proof screws, and specialty mounts/pendants are available upon request.

### LETTERS

- 6" high; 0.75" stroke

### ARROWS

- NFPA type, universal field-selectable chevrons

### WEIGHT

- 4.5 lbs

### CANOPY SIZE

- 4.75" x 4.75" x 0.75"

### TEMPERATURE RATING

- 50°F to 122°F (10°C to 40°C)

### APPROVALS

- UL 924
- CEC Title 20 Compliant
- NFPA 101 Life Safety Code
- NFPA 70-NEC
- OSHA

### WARRANTY

- Isolite offers a lifetime warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.

## DIMENSIONS

