

DATE:	COMMENTS:
PROJECT:	

FEATURES

- Includes a 6" International Symbol of Accessibility or Dynamic Symbol of Accessibility.
- Long life nickel cadmium maintenance free battery provides the required 90 minutes of emergency operation.
- Solid state transfer relay uses no relay contacts to reduce oxidization and failure in order to ensure reliability.
- An electronic control circuit and an isolation transformer provides current control and circuit protection for high output, energy efficient LED technology.
- Line-latch prevents unnecessary discharge of battery during installation. Loads will not illuminate until after application of utility power.
- Brownout detection ensures emergency operation during periods of low line voltage.
- LED indicator is used to indicate AC presence.
- A push-to-test switch can be used to test the emergency operation.
- 120/277 VAC with field selectable inputs.

SYMBOL KEY



CLICK THE IMAGE TO VIEW ALTERNATE PRODUCT PHOTOS
Only available with Adobe Acrobat and Acrobat Reader



DSA = Dynamic Symbol of Accessibility (CT)



ISA = International Symbol of Accessibility (MA)

ORDERING INFORMATION *ECTMA-AC-G-1C-DSA-BA-MB*

1. SERIES	2. OPERATION	3. COLOR	4. FACE COUNT	5. SYMBOL
ECTMA	-	-	-	-
	AC AC Only EM Ni-Cad Battery Backup	G Green R Red	1C Single Face, Clear Background 1M Single Face, Mirror Background 1W Single Face, White Background 2M Double Face, Mirror Background 2W Double Face, White Background	DSA Dynamic Symbol of Accessibility (CT) ISA International Symbol of Accessibility (MA)
6. FRAME COLOR	7. MOUNTING	8. OPTIONS		
BA Brushed Aluminum Frame WH White Frame	MB Back Mount (Surface Wall) ME End Mount / Side Mount MP Pendant Mount MRC Recessed Ceiling Mount MRW Recessed Wall Mount MT Top Mount	BLANK = NO OPTION EB Extended Run Time		

ACCESSORIES; ORDER SEPARATELY

- **MP** = 12" Pendant Kit

SPECIFICATIONS
CONSTRUCTION

- Durable, 20 gauge steel
- White-baked powder coat finish
- High clarity acrylic

LETTERS

- 6" high; 0.75" stroke

ARROWS

- NFPA-type, universal field selectable chevrons.

WEIGHT

- 6 lb

TEMPERATURE RATING

- From 50°F to 113°F

APPROVALS

- CSA-US listed
- Meets or exceeds UL 924 standards
- State of Connecticut Building Code Paragraph 1011.1.2
- NFPA 101 Life Safety Code
- NFPA 70-NEC
- OSHA
- BAA Compliant

WARRANTY

- Isolite offers a 5-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website. Lamps not warranted.

DIMENSIONS
