



EDC-NYC

New York City Approved Economical Die-Cast LED Exit Sign

DATE:

PROJECT

COMMENTS:

FEATURES

- Approved in New York City using 8" lettering and 1" stroke.
- Ultra-bright, energy efficient, long-life red LEDs.
- Internal solid-state transfer switch automatically connects the internal battery to LED board and LED lamp heads for minimum 90-minute emergency illumination.
- Full automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours while reducing overcharge and improving the life of the battery.
- 4.8V long-life, maintenance-free, rechargeable nickel cadmium battery.
- Charge rate/power "ON" LED indicator light and push-to-test switch are provided for mandated code compliance testing.
- 120/277 VAC with field selectable inputs (with the exception of dual circuit models).
- Premium-grade, aluminum housing with field selectable knockout chevron directional indicators.



CLICK THE IMAGE TO VIEW ALTERNATE PRODUCT PHOTOS
Only available with Adobe Acrobat and Acrobat Reader

ORDERING INFORMATION EDC-NYC-AC-R-1-BA-BA-MTEBP

1. SERIES EDC-NYC	2. OPERATION - AC AC Only EM Ni-Cad Battery Backup	3. ILLUMINATION - R Red	4. FACE COUNT - 1 Single 2 Double U Universal	5. FACE COLOR - BA Brushed Aluminum BK Black WH White
6. FRAME COLOR BA Brushed Aluminum BK Black WH White	7. MOUNTING - MTEBP Universal Mount	8. OPTIONS BLANK = NO OPTION CX Dual Circuit (120/277 VAC) (AC Only) SD Self-Diagnostics (EM Only) TP Tamperproof Screws		

SPECIFICATIONS

CONSTRUCTION

- Premium-grade, aluminum housing available in black or white powder-coat finishes.

ARROWS

- Field selectable knockout chevron directional indicators

WEIGHT

- 5 lbs

TEMPERATURE RATING

- From 32°F to 122°F

APPROVALS

- New York City Approved
- UL 924
- UL Listed for Damp Location
- NFPA Life Safety Code 101
- NFPA 70-NEC
- OSHA
- CEC Title 20 Compliant

WARRANTY

- Isolite offers a 5-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website. Lamps not warranted.

ACCESSORIES ON BACK

ACCESSORIES; ORDER SEPARATELY

- **WG-16.5LX14.0WX6.0D** = Wireguard, Length: 16.5", Width: 14", Depth: 6"
- **WG-20.0LX19.0WX9.0D** = Wireguard, Length: 20", Width: 19", Depth: 9"
- **WG-26.0LX19.0WX9.0D** = Wireguard, Length: 26", Width: 19", Depth: 9"

DIMENSIONS