



# LPX-CTMA

Connecticut & Massachusetts Aluminum LED Mobility Exit Sign

DATE:	COMMENTS:
PROJECT:	

## FEATURES

- Complies with the State of Connecticut Building Code requirements and provides an exit sign with a 6.0" International Symbol of Accessibility.
- Universal mounting pattern is stamped into the back plate for easy surface mounting to a j-box.
- Long life, maintenance-free nickel cadmium battery provides the required 90 minutes of emergency operation.
- Electronic control circuit and isolation transformer provide current control and circuit protection, ensuring optimum LED efficiency and life.
- Solid-state transfer relay ensures the relay contacts do not oxidize or fail resulting in high reliability.
- Uses energy efficient LEDs with high output.
- Line-latch prevents unnecessary discharge of battery during installation. Loads will not illuminate until after application of utility power.
- Brownout detection ensures emergency operation during periods of low line voltage.
- LED AC indicator and push-to-test switch are provided standardly.
- 120/277 VAC with field selectable inputs.



CLICK THE IMAGE TO VIEW ALTERNATE PRODUCT PHOTOS  
Only available with Adobe Acrobat and Acrobat Reader

## SYMBOL KEY



DSA = Dynamic Symbol of Accessibility (CT)



ISA = International Symbol of Accessibility (MA)

## ORDERING INFORMATION *LPX-CTMA-AC-G-DSA-1-BA-MB*

1. SERIES	2. OPERATION	3. ILLUMINATION	4. SYMBOL	5. FACE COUNT
LPX-CTMA	-	-	-	-
	AC AC Only EM Ni-Cad Battery Backup	G Green R Red	DSA Dynamic Symbol of Accessibility (CT) ISA International Symbol of Accessibility (MA)	1 Single 2 Double U Universal
6. FRAME COLOR	7. MOUNTING	8. OPTIONS		
BA Brushed Aluminum BK Black WH White	MTEBP Universal Mount MPAB 12" Swivel Mount (Black) MPABA 12" Swivel Mount (Brushed Aluminum) MPAW 12" Swivel Mount (White)	BLANK = NO OPTION EB Extended Run-time (EM Only) TP Tamper Proof Screws		

## ACCESSORIES; ORDER SEPARATELY

- WG-20.0LX19.0WX9.0D** = Wireguard, Length: 20", Width: 19", Depth: 9"
- WG-26.0LX19.0WX9.0D** = Wireguard, Length: 26", Width: 19", Depth: 9"



## SPECIFICATIONS

### CONSTRUCTION

- Durable, extruded aluminum

### LETTERS

- 6.0" high; 0.75" stroke

### ARROWS

- NFPA-type, universal field selectable chevrons.

### WEIGHT

- AC: 4.7 lbs
- EM: 5.2 lbs

### TEMPERATURE RATING

- From 50°F to 113°F

### APPROVALS

- CSA-US listed
- Tested to UL 924 Standards
- State of Connecticut Building Code Paragraph 1011.1.2
- NFPA 101 Life Safety Code
- NFPA 70-NEC
- OSHA
- BAA Compliant

### WARRANTY

Isolite offers a 5-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website. Lamps not warranted.

## DIMENSIONS

