

DATE:

COMMENTS:

PROJECT:

FEATURES

- Activation requires only 5 foot-candles (54 lux) of unfiltered fluorescent, LED, metal halide, or mercury vapor lighting for 60 minutes (must be externally illuminated during normal building occupation).
- PH100 tested and listed per UL924 requirements for use with LED lighting.
- The photoluminescent material allows for a 100' viewing distance.
- Suitable for use in damp and hazardous locations.
- The life expectancy is 25+ years.
- Universal chevrons are field installable.
- No electrical connections are needed for operation.
- Installation is fast, easy, and maintenance free.



CLICK THE IMAGE TO VIEW ALTERNATE PRODUCT PHOTOS
Only available with Adobe Acrobat and Acrobat Reader

ORDERING INFORMATION *PHP100-1-WH-MTEB*

PHP100-1-WH-MTEB PHP100 100' Photoluminescent LED Charged Exit Sign, Single Face Count, White, Top/End/Back Mount

PHP100-2-WH-MTEB PHP100 100' Photoluminescent LED Charged Exit Sign, Double Face Count, White, Top/End/Back Mount

ACCESSORIES; ORDER SEPARATELY

- **WG-20.0LX19.0WX9.0D** = Wireguard, Length: 20", Width: 19", Depth: 9"
- **WG-26.0LX19.0WX9.0D** = Wireguard, Length: 26", Width: 19", Depth: 9"

SPECIFICATIONS

CONSTRUCTION

- Durable ABS panel

APPROVALS

- UL 924
- NFPA 101 Life Safety Code
- NFPA 70-NEC
- OSHA

WARRANTY

Isolite offers a 3-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.

DIMENSIONS

