

DATE:	COMMENTS:
PROJECT:	

FEATURES

- Thin architectural profile constructed with die-cast aluminum with specialty finishes available.
- Illuminates 7 times brighter than UL 924 requirement with super-bright, long-life LEDs and a 25+ year life expectancy.
- Battery back-up models without remote heads have a standard 4 hour runtime.
- UL listed for damp locations.
- Optional polycarbonate security cover is available (see accessories).
- Self-Test / Self-Diagnostic monitoring is available.
- Line latch prevents unnecessary discharge of battery during installation. Loads will not illuminate until after application of utility power.
- Brownout detection ensures emergency operation during periods of low line voltage.
- Sealed, external, momentary test switch and dual diagnostic LED indicator display AC presence and Hi-Charge status.
- Zero current low-voltage disconnect used to prevent battery from being overly discharged.
- Unique, electronic driver circuit provides current control and protection, ensuring optimum LED efficiency and life.
- 120/277 VAC with field selectable inputs.



ORDERING INFORMATION *TLCG2-AC-R-WH-1-BA-MB*

1. SERIES	2. OPERATION	3. ILLUMINATION	4. BACKGROUND COLOR	5. FACE COUNT	6. FRAME COLOR														
TLCG2	-	-	-	-	-														
	AC AC Only EM Ni-Cad Battery Backup	G Green R Red W White BL Blue	BL Blue Background BK Black Background WH White Background CC Custom Color	1 Single 2 Double	BA Brushed Aluminum BK Black CC Custom Color WH White														
7. MOUNTING	8. OPTIONS																		
MB Back Mount MPA 12" Pendant Mount MPB 24" Pendant Mount MPC 36" Pendant Mount MPD 48" Pendant Mount MPE 60" Pendant Mount MPF 72" Pendant Mount MTEB Top/End/Back Mount	BLANK = NO OPTION CX Dual Circuit (120/277 VAC) (AC Only) SD Self-Diagnostics (EM Only) SR Self-Diagnostics + IR Remote Testing Receiver (EM Only) EB Remote Capacity (EM Only) CW Custom Wording CW01 X-Ray In Use CW02 In Use	<table border="1"> <tr> <td>CW03</td> <td>Area of Refuge</td> </tr> <tr> <td>CW04</td> <td>Laser in Use</td> </tr> <tr> <td>CW06</td> <td>Beam On</td> </tr> <tr> <td>CW26</td> <td>Area of Rescue Assistance</td> </tr> <tr> <td>FL</td> <td>Flasher</td> </tr> <tr> <td>FA</td> <td>Fire Alarm Interface</td> </tr> <tr> <td>VR</td> <td>1/8" Vandal Resistant Lens (Includes TP)</td> </tr> </table>				CW03	Area of Refuge	CW04	Laser in Use	CW06	Beam On	CW26	Area of Rescue Assistance	FL	Flasher	FA	Fire Alarm Interface	VR	1/8" Vandal Resistant Lens (Includes TP)
CW03	Area of Refuge																		
CW04	Laser in Use																		
CW06	Beam On																		
CW26	Area of Rescue Assistance																		
FL	Flasher																		
FA	Fire Alarm Interface																		
VR	1/8" Vandal Resistant Lens (Includes TP)																		

ACCESSORIES; ORDER SEPARATELY

- WG-16.5LX14.0WX3.0D** = Wireguard, Length: 16.5", Width: 14", Depth: 3"
- WG-16.5LX14.0WX6.0D** = Wireguard, Length: 16.5", Width: 14", Depth: 6"
- WG-20.0LX19.0WX9.0D** = Wireguard, Length: 20", Width: 19", Depth: 9"
- WG-26.0LX19.0WX9.0D** = Wireguard, Length: 26", Width: 19", Depth: 9"
- TLRT** = Infrared Remote Control

SPECIFICATIONS

CONSTRUCTION

- Injection molded, internal cavity reflector provides ease of installation and maintenance, together with perfectly even legend illumination.
- Heavy duty, two piece walls are constructed from die cast aluminum alloy.
- Removable front stencil face includes overlapping light seal.

TEMPERATURE RATING

- From 50°F to 104°F

APPROVALS


- UL 924
- UL 924 Damp Location
- NFPA 101 Life Safety Code
- NFPA 70-NEC
- OSHA

WARRANTY


Isolite offers a 5-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.

DIMENSIONS

Single or Double face sign



NOMENCLATURE



CUSTOM GRAPHICS

01 	02 	03 	04 	05 
06 	07 	08 	09 	10 
11 	12 	13 	14 	15 
16 	17 	18 	19 	20 
21 	22 	23 	24 	25 
26 	27 	28 	29 	30 
31 	32 	33 	<p>NOTE For signs requiring directional indicators, select C custom letter and specify graphic with chevron direction.</p>	

CUSTOM GRAPHICS


CW01



CW02




CW03



CW04



CW06



CW26

