



TLREM2

Aluminum Thin Line Die-Cast Remote LED Exit Sign

| | |
|----------|-----------|
| DATE: | COMMENTS: |
| PROJECT: | |

FEATURES

- Remote exit sign is designed to be powered by a master exit sign like the TLRM2, LPDCMR, or ELTMR2.
- Thin architectural profile constructed with die-cast aluminum with specialty finishes available.
- Illuminates 7 times brighter than UL 924 requirement with super-bright, long-life LEDs that have a 25+ year life expectancy.
- UL listed for damp locations.
- Optional polycarbonate security cover is available (see accessories).
- Available with low profile universal mount, back mount, or pendant mount.
- All mountings use standard 4S junction box (not included).
- Unique, electronic driver circuit provides current control and protection, ensuring optimum LED efficiency and life.

CEC Title 20



CLICK THE IMAGE TO VIEW ALTERNATE PRODUCT PHOTOS

Only available with Adobe Acrobat and Acrobat Reader

ORDERING INFORMATION TLREM2-G-1-BA-MB

| 1. SERIES | 2. ILLUMINATION | 3. FACE COUNT | 4. FRAME COLOR | 5. MOUNTING |
|-----------|------------------|-------------------------------------|----------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| TLREM2 | - | - | - | - |
| | G Green R Red | 1 Single 2 Double U Universal | BA Brushed Aluminum BK Black CC Custom Color WH White | MB Back Mount MPA 12" Pendant Mount MPB 24" Pendant Mount MPC 36" Pendant Mount MPD 48" Pendant Mount MPE 60" Pendant Mount MPF 72" Pendant Mount MTEB Top/End/Back Mount |

6. OPTIONS

BLANK = NO OPTION

VR 1/8" Vandal Resistant Lens (Includes TP)

ACCESSORIES; ORDER SEPARATELY

- WG-16.5LX14.0WX3.0D = Wireguard, Length: 16.5", Width: 14", Depth: 3"
- WG-16.5LX14.0WX6.0D = Wireguard, Length: 16.5", Width: 14", Depth: 6"
- WG-20.0LX19.0WX9.0D = Wireguard, Length: 20", Width: 19", Depth: 9"
- WG-26.0LX19.0WX9.0D = Wireguard, Length: 26", Width: 19", Depth: 9"



SPECIFICATIONS

CONSTRUCTION

- Injection molded, internal cavity reflector provides easy installation and maintenance together with perfectly even legend illumination.
- Heavy-duty, two piece walls are constructed from die-cast aluminum alloy.
- Removable front stencil face includes overlapping light seal.

LETTERS

- 6.0" high; 0.75" stroke

ARROWS

- NFPA type, universal field-selectable chevrons.

TEMPERATURE RATING

- From 50°F to 104°F

APPROVALS

- UL 924
- CEC Title 20 Compliant
- UL 924 Damp Location
- NFPA 101 Life Safety Code
- NFPA 70-NEC
- OSHA

WARRANTY

Isolite offers a 5-year limited warranty. For further details, refer to General Warranty and Obligations in the Isolite manual or on our website.

DIMENSIONS

